FITMENT INSTRUCTIONS





Tread Door Lock Cover Fitment Instructions

All rights reserved. No part of this document may be reproduced, translated, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without prior written permission of the owner.

Review all instructions information carefully before installation.

Any damages, direct or incidental to the installer and/or property due to incorrect installation of any parts are the responsibility of the installer. Due to the various applications and fitment options available, the responsibility lies with the user to ensure all mounting points are secure and tight before every trip. If unsure, consult with your Distributor regarding the operations of our products.

Users are advised to be mindful of the load they are carrying and drive in accordance with road conditions.

DISCLAIMER



1. Tread Door Lock Cover Fitment - Tools & Equipment

The table below show the equipment, i.e. tools and rivets required to start the fitment.

ITEM	QTY
Canopy Lock Cover	1
8mm Spanner	1

1. To install the Lock Cover, the push-lock will need to be taken out by removing the back cover and so that you have the parts separate, as seen below:



*PLEASE NOTE: This accessory is not recommended for older canopy or camper models with glued-in push-locks. Should you have an older model canopy with a sealed-in lock, contact Alu-Cab HQ for assistance on queries@alu-cab.co.za.

2. Position the Push Button Gasket over the opening:



3. Position the Lock Cover on top of the Push Button Gasket:



4. Place the push-lock back in position:



5. Bolt the back-cover back into place:





WARNING

Always wear appropriate PPE (Personal protection equipment) when fitting this product. Although the mounting kit is designed to be DIY, if you have any doubts or concerns, contact an accredited fitment centre to carry out the work. Alu-Cab will not be liable for any injury to persons, and/or damage to products and/or vehicles.